

# H-100

## 100 Watt Ultra Rad-Hard LED Luminaire

*LOCA certified  
Seismic certified  
Radiation certified  
ILRT certified  
CB, CE, FCC certified*

Product flyer, Version 2.4, June 2024

## Nuclear grade High-Bay LED Luminaire.

**H-100** is a member of extremely high radiation, high temperature resistant series of LED Lighting products, proudly created and made by DITO Lighting, Slovenia, EU.

**H-100** is a nuclear grade High-Bay LED Luminaire, designed to be used in high radiation, high temperature areas. The housing of the Luminaire is made of stainless steel. The product is **LOCA** and **seismic** tested and certified.

Typical application for the **H-100** is High-Bay lighting inside the RB of the NPP.

**H-100** is tested for TID of **500 kGy** gamma, combined with  **$5 \times 10^{14}$  neutron/cm<sup>2</sup> 1MeV (Si)** equivalent neutron fluence.

**H-100** is small, light, extremely efficient 100 W LED Luminaire, designed for simple one-to-one replacement of the existing mature lighting technologies.

The power electronics, i.e. driver is located inside the Luminaire, **without any external boxes** mounted elsewhere outside radiation zone - true "all-in-one" solution. In most cases upgrading existing mature lighting requires no changes to existing wiring, greatly reduces time and costs of installation.



**H-100** uses silicone optics. Silicone optics is flexible, has operational temperature range of over 200 °C, is 100 % shatter proof, browning proof and chemically stable.

The product is fully potted, without any trapped air inside, therefore insensitive to external pressure changes - **ILRT** compatible.

Internal electronics is soft mounted, protected against seismic shocks, vibrations, liquids, hot steam and most chemicals.

For latest, up to date information please visit:

[www.dito-lighting.com](http://www.dito-lighting.com)  
[nuclear@dito-lighting.com](mailto:nuclear@dito-lighting.com)



DITO Lighting reserves the right to make changes without prior notice.

DITO Lighting logo is registered trademark.

**H-100** is registered model.

Copyright © DITO Lighting 2024. All rights reserved.



# H-100

## 100 Watt Ultra Rad-Hard LED Luminaire



### Specifications:

Rated power:	100 W
Available voltages:	100, 120, 220, 230, 277 V
Power factor:	> 0.9
Luminous flux:	> 16.000 lm
CCT:	5000 K
CRI:	> 80
Luminaire efficacy:	> 160 lm/W
Electronics location:	internal
Housing material:	Stainless Steel
Optics material:	Silicone
Ingress protection:	IP 68 / IP 69K
Impact protection:	IK 08
Ambient temperature:	-20 °C to +60 °C
Weight:	5.8 kg
Dimensions:	dia 320 × 208 mm
Warranty:	5 years

### In compliance with (partial list):

MIL-STD-883, Method 1017 neutrons  
MIL-STD-883, Method 1019 gamma  
ESA ESCC No. 22900 gamma  
IEEE 344 -2013  
IEC 60980  
2014/30/EU (EMC)  
2014/35/EU (LVD)

### Radiation tolerance:

Gamma:	$5 \times 10^5$ Gy
Neutrons 1MeV (Si):	$5 \times 10^{14}$ n/cm <sup>2</sup>

### LOCA compatibility:

Ambient operational:	80 °C/350 h
Ambient non operational:	140 °C/24 h

### Reliability (environment: GB @ 50 °C):

Calculation method:	MIL-217F N2
MTBF:	3.758.857 h
Predicted lifetime:	> 22 years
Confidence level:	95 %

### Notes:

Irradiation tests performed inside the core of the TRIGA MkII nuclear research reactor with the representative NPP spectrum.

Different input voltages versions are available: 100, 120, 220, 230 and 277 VAC/VDC. Mains frequency can vary between 45 and 65 Hz. The Luminaire supports both AC and DC voltage, but does not support wide input voltage range.

The Luminaire is designed for professional use only.